



KBAD 45 (2024)




Oil Pattern Distance	45	Reverse Brush Drop	40	Oil Per Board	50 uI
Forward Oil Total	15.3 mL	Reverse Oil Total	10.35 mL	Volume Oil Total	25.65 mL
Tank Configuration	A Only	Tank A Conditioner	ICE	Tank B Conditioner	FIRE

	START	STOP	LOADS	SPEED	CROSSED	START	END	FEET	T.OIL
1	4L	4R	2	14	66	0.0	1.9	1.9	3300
2	4L	4R	3	18	99	1.9	9.5	7.6	4950
3	9L	9R	3	18	69	9.5	17.1	7.6	3450
4	14L	14R	3	18	39	17.1	24.7	7.6	1950
5	15L	15R	3	18	33	24.7	32.3	7.6	1650
6	4L	4R	0	26	0	32.3	36.0	3.7	0
7	4L	4R	0	30	0	36.0	45.0	9.0	0

	START	STOP	LOADS	SPEED	CROSSED	START	END	FEET	T.OIL
1	2L	2R	0	30	0	45.0	36.0	-9.0	0
2	14L	14R	2	22	26	36.0	29.8	-6.2	1300
3	13L	13R	2	18	30	29.8	24.7	-5.1	1500
4	12L	12R	2	18	34	24.7	19.6	-5.1	1700
5	11L	11R	2	18	38	19.6	14.5	-5.1	1900
6	9L	9R	2	18	46	14.5	9.4	-5.1	2300
7	4L	4R	1	18	33	9.4	6.9	-2.5	1650
8	4L	4R	0	14	0	6.9	0.0	-6.9	0

Cleaner Ratio Main Mix NA Forward
Cleaner Ratio Back End Mix NA Reverse
Cleaner Ratio Back End Distance NA Combined
Buffer RPM: 4 = 700 | 3 = 500 | 2 = 200 | 1 = 100



Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
Description	Outside:Middle	Middle:Middle	Inside:Middle	Middle: Inside	Middle:Middle	Middle:Outside
Track Zone Ratio	5.21	2.23	1.1	1.1	2.23	5.21

