



KBAD 38 (2024)



Oil Pattern Distance	38	Reverse Brush Drop	37	Oil Per Board	55 ul
Forward Oil Total	14.63 mL	Reverse Oil Total	6.71 mL	Volume Oil Total	21.34 mL
Tank Configuration	A Only	Tank A Conditioner	ICE	Tank B Conditioner	FIRE

	START	STOP	LOADS	SPEED	CROSSED	START	END	FEET	T.OIL
1	2L	2R	2	14	74	0.0	1.9	1.9	4070
2	6L	6R	1	18	29	1.9	4.4	2.5	1595
3	8L	8R	1	22	25	4.4	7.5	3.1	1375
4	10L	10R	2	22	42	7.5	13.7	6.2	2310
5	11L	11R	3	26	57	13.7	24.7	11.0	3135
6	14L	14R	3	26	39	24.7	35.7	11.0	2145
7	2L	2R	0	26	0	35.7	38.0	2.3	0

	START	STOP	LOADS	SPEED	CROSSED	START	END	FEET	T.OIL
1	2L	2R	0	30	0	38.0	35.0	-3.0	0
2	14L	14R	2	26	26	35.0	27.7	-7.3	1430
3	11L	11R	2	22	38	27.7	21.5	-6.2	2090
4	8L	8R	1	18	25	21.5	19.0	-2.5	1375
5	4L	4R	1	18	33	19.0	16.5	-2.5	1815
6	2L	2R	0	14	0	16.5	0.0	-16.5	0

Cleaner Ratio Main Mix NA Forward
Cleaner Ratio Back End Mix NA Reverse
Cleaner Ratio Back End Distance NA Combined
Buffer RPM: 4 = 700 | 3 = 500 | 2 = 200 | 1 = 100

Cleaner Ratio Main Mix 5:1 Forward
Cleaner Ratio Back End 5:1 Reverse

Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
Description	Outside:Middle	Middle:Middle	Inside:Middle	Middle:Inside	Middle:Middle	Middle:Outside
Track Zone Ratio	5.63	1.96	1.06	1.06	1.96	5.63

